SONANCE

VISUAL EXPERIENCE DATA SHEET

## VX46R

TECHNICAL SPECIFICATIONS

|	**VX46R**
SKU	96010 - Pair
Tweeter	0.75" (19mm) ceramic dome, Ferrofluid-cooled, acoustic back chamber
Woofer	4.5" (114mm) Kevlar/Nomex cone, rubber surround, pivoting
Dispersion Technology	Sinusoidal textured waveguide
Speaker Pivot	Coincident woofer and tweeter, +/-13° pivot
Frequency Response	58Hz - 20kHz +/-3dB
Impedance	8 ohms nominal; 6 ohms minimum
Power Handling (RMS)	5 watts minimum; 80 watts maximum
Sensitivity (2.83V/1m)	90dB SPL
Mounting Technology	Flex Frame 1 or 2-stage, 3 x RotoLock® Clamps
Round Micro Trim Grille (Dia)	6.77" (171.8mm)
Round Trimless Grille (Dia)	6.42" (163mm)
Square Micro Trim Grill (WxH)	6.77" x 6.77" (171.8mm x 171.8mm)
Square Trimless Grille (WxH)	6.42" x 6.42" (163mm x 163mm)
Speaker Mounting Depth (D)	4.61" (117.1mm)
Mounting Depth + Retrofit Encl.	5.75" (146.1mm)
Cut-Out Dims (Dia)	5.875" (149mm)
Shipping Weight	6 lbs. (2.8kg)

DIMENSIONAL DRAWINGS

Cut-Out Diameter
Front View

Mounting Depth (Open Back)
Side View

Mounting Depth + Retrofit Enclosure
Side View

VX 4" ROUND ACCESSORIES

VX4R-GRILLE-T 4" Micro Trim Round Grille / Pair		93573
VX4R-GRILLE-NT 4" Trimless Round Grille / Pair		93574
VX4SQ-T 4" Micro Trim Square Adapter / Pair		96029
VX4SQ-T-5PR 4" Micro Trim Square Adapter / 5xPair		96032
VX4SQ-NT 4" Trimless Square Adapter / Pair		93585
VX4SQ-NT-5PR 4" Trimless Square Adapter / 5xPair		93588
VX4-ENCL-R 4" Round Enclosure / Pair		96443
FLEXBRK-4-R 4" Round Flex Bracket / 5x Pair		92471