SONANCE

VISUAL EXPERIENCE DATA SHEET

VX66R SST

TECHNICAL SPECIFICATIONS

VX66R SST SKU 93684 - Fach

1" (25mm) ceramic dome, Ferrofluid-cooled, acoustic back chamber, dual voice coil **Tweeter**

6.5" (165mm) Kevlar/Nomex cone, rubber surround, pivoting, dual voice coil Woofer

43Hz - 20kHz +/-3dB Frequency Response

8 ohms nominal; 6 ohms minimum Impedance

Power Handling (RMS) 5 watts minimum; 140 watts maximum


90dB SPL Sensitivity (2.83V/1m)

Square Micro Trim Grille (WxH) 9.62" (244.4mm) 9.28" (235.6mm) Square Trimless Grille (WxH)


Square Micro Trim Grille (WxH) 9.62" x 9.62" (244.4mm x 244.4mm) 9.28" x 9.28" (235.6mm x 235.6mm) Square Trimless Grille (WxH)

4.92" (125mm) Speaker Mounting Depth (D) 5.75" (146.1mm) Mounting Depth + Retrofit Encl. 8.25" (210mm) Cut-Out Dims (Dia) 4.5 lbs. (2.1kg) **Shipping Weight**

DIMENSIONAL DRAWINGS




Cut-Out Width **Front View**



Mounting Depth (Open Back)

Side View



Mounting Depth + Retrofit Enclosure

Side View

VX 6" ROUND ACCESSORIES

WCD CDULET	
VX6R-GRILLE-T	07575
6" Micro Trim Round Grille / Pair	93575
VX6R-GRILLE-NT	
6" Trimless Round Grille / Pair	93576
VX6SQ-T	
6" Micro Trim Square Adapter / Pair	96030
VX6SQ-T-5PR	00000
6" Micro Trim Square Adapter / 5xPair	96033
VX6SQ-NT	90033
	07500
6" Trimless Square Adapter / Pair	93586
VX6SQ-NT-5PR	
6" Trimless Square Adapter / 5xPair	93589
VX6-ENCL-R	
6" Round Enclosure / Pair	96343
FLEXBRK-6-R	
6" Round Flex Bracket / 5x Pair	92337
o Round Flex Blacket / 3x Pair	52337

LIMITED LIFETIME WARRANTY