

XDS Speaker Range

The XDS Range of speaker enclosures represent our top of the line offering from Australian Monitor. They can be used in either front of house applications or as foldback monitors and have been acclaimed for their musical fidelity for use in bands or as general sound reinforcement enclosures.

Features

- M10 fly points
- M10 rear bracket wall mount point
- 35mm stand boot
- Connection via a pair of 4 pole Speakon or screw terminal block
- Recessed carry handle
- U bracket available
- Rubber feet fitted
- Can be used as a foldback wedge



SPECIFICATIONS

	XDS8	XDS10	XDS12
Impedance (Nominal)	8 Ohms	8 Ohms	8 Ohms
Power (Continuous)	100 Watts	250 Watts	300 Watts
Sensitivity (1 W / 1 M)	92 dB	94 dB	96 dB
Calculated Max SPL	112 dB	118 dB	121 dB
Dispersion (-6 dB Points) (H x V)	100° x 100° non-rotatable	50-100° x 50° rotatable	80° x 50° rotatable
Frequency Response (-3dB)	80 Hz - 20 kHz	55 Hz - 20 kHz	50 Hz - 18 kHz
Frequency Response (-10dB)	70 Hz - 20 kHz	50 Hz - 20 kHz	45 Hz - 20 kHz
Connection	4 pole twist lock connectors (x2) screw terminal strip (x2)	4 pole twist lock connectors (x2) screw terminal strip (x2)	4 pole twist lock connectors (x2) screw terminal strip (x2)
Components	1 x 8" Woofer, 1 x 1.35" HF Driver	1 x 10" Woofer, 1 x 1.35" HF Driver	1 x 12" Woofer, 1 x 1.7" HF Driver
Net Dimensions (w x d x h)	293 mm x 284 mm x 408 mm (11.5" x 11.2" x 16.1")	348.6 mm x 328 mm x 502 mm (13.7" x 12.9" x 19.8")	396 mm x 396.4 mm x 620 mm (15.6" x 15.6" x 24.4")
Shipping Dimensions (w x d x h)	350mm x 350 mm x 470 mm (13.8" x 13.8" x 18.5")	430 mm x 410 mm x 605 mm (16.9" x 16.1" x 23.8")	480 mm x 480 mm x 720 mm (18.9" x 18.9" x 28.3")
Net Weight	10 kg 22.0 (lbs)	16.5 kg 36.3 (lbs)	20 kg 44.0 (lbs)
Shipping Weight	11.5 kg 25.3 (lbs)	18.5 kg 40.7 (lbs)	23 kg 50.6 (lbs)

	XDS115	XDS212
Impedance (Nominal)	8 Ohms	8 Ohms
Power (Continuous)	300 Watts	600 Watts
Sensitivity (1W / 1M)	96 dB	99 dB
Calculated Max SPL	121 dB	127 dB
Frequency Response (-3dB)	35 Hz - 500 Hz	50 Hz - 180 Hz
Frequency Response (-10dB)	30 Hz - 500 Hz	45 Hz - 180 Hz
Connection	4 pole twist lock connectors (x2)	4 pole twist lock connectors (x2)
Components	1 x 15" Woofer	2 x 12" Woofers
Net Dimensions (w x d x h)	512 mm x 600 mm x 650 mm (20.1" x 23.6" x 25.6")	512 mm x 600 mm x 680 mm (20.1" x 23.6" x 26.8")
Shipping Dimensions (w x d x h)	700 mm x 615 mm x 750 mm (27.6" x 24.2" x 29.5")	700 mm x 615 mm x 780 mm (27.6" x 24.2" x 30.7")
Net Weight	30 kg 66.0 (lbs)	40 kg 88.0 (lbs)
Shipping Weight	35 kg 77.0 (lbs)	45 kg 99.0 (lbs)



ENGINEERED BY AUSTRALIAN MONITOR

Address: 1 Clyde Street, Silverwater NSW 2128 Australia.

Website: www.australianmonitor.com.au

International enquiries email: customersupport@australianmonitor.com.au

ABN 35 007 573 417